



MMM Group


CLIMACELL[®] EVO

Climatic Chamber with Forced Air Circulation,
Cooling and Controlled Humidity

NEW



Innovative Heat Technology



protecting human health

Tradition, Quality,
Innovation

Since its establishment in 1921, BMT Medical Technology s.r.o., the traditional manufacturer of medical and laboratory technology, has been gradually transformed from a small regional company to an international corporation.

In 1992, it became a member of the European MMM Group which has been operating on the world markets since 1954 as an important supplier of systems for the health care industry, science and research. With its comprehensive offer of products and services, sterilization and disinfection devices for hospitals, scientific institutes, laboratories and pharmaceutical industry, MMM Group has established itself as an outstanding quality and innovations producer on the global markets.

The knowledge and experience gained during the implementations of individual supplies for our customers all over the world, and the technical innovations have been permanently and positively influencing the development, construction and production of our devices. High level of our work has also been confirmed by the number of patents and industrial designs as well as an easy implementation of individual device adjustments.

MMM Group – excellence
in medical and laboratory
technology.

Basic Characteristics

- Volume:** 111, 222, 404, 707, 1 212 liters
- Temperature range:**
with humidity 10°C to 90°C,
without humidity 0°C to 100°C
(options of –20°C and +160°C
decontamination)
- Humidity range:** 10–98%
- Refrigerant:**
R404a (down to –20°C),
R134a (down to 0°C)
- Requested water quality:**
demineralized water <8 µS/cm
- Source of water:**
Water deposit (included)
or central water piping <0,5 bar
- Sealing inner glass door**
- Interior:** stainless steel,
mat. No. 1.4301 (AISI 304)

CLIMACELL® EVO

Climatic Chamber With a Wide Range of Applications

The device CLIMACELL® is designed for applications requiring exact and reproducible simulation of variable climatic conditions. The basic version of the incubator allows simultaneous regulation of temperature and humidity. In case of optional equipment buying, the device offers regulation of CO₂ respectively other gases concentration or space-homogenous lighting in the field of visible or UV light with adjustable intensity and possibility of intensity measuring using special probes. Thanks to the unique combination, the device offers a wide range of possible applications to users. CLIMACELL® can be used in biology, food processing, chemical industry, electrical technology, histology, botany, pharmacy and in other branches. As a typical example it is possible to state cultivation of plant and tissue cultures or stability (photo-stability) tests of materials and medicaments. Simple control via touch screen, exact regulation and many possibilities of data outputs meet the most demanding conditions of pharmaceutical industry and they also allow user-friendly simulation of simple requirements towards plants growing. Microprocessor-controlled system of humidification and dehumidification together with high-performance programmable system of exposition lighting guarantees excellent homogenous parameters for tests and growth conditions.

Meeting the requirements of regulations
2006/95/EC, 2004/108/EC, ICH 279/95 Option 2, FDA 21 part 11.



Applications



Pharmaceutical Industry

Stability testing and photo stability testing according to ICH 279/95 Option 2, long term storage



Cosmetic Industry

Durability testing, testing of cosmetic products or primary materials stability



Construction Industry

Long-term testing of quality and ageing of materials in construction industry – cement, paints, asphalt, construction plastics, glues, etc.



General and Applied Industry
(research field)

E.g. cultivation of tissue cultures – human or animal ones



Food and Beverage Industry

Testing of food quality under simulated transport or storage conditions – export of fruits, etc.



Packaging Material Industry

Long-term testing of packing technologies



Electronic Industry

Durability testing of electronic boards and printed circuits



Automotive Industry

Testing of materials ageing – tyres, sealing, etc.



Zoology

Simulation of conditions for sea organisms research – seaweed or cultivation of insect eggs.



Botany

Studies of germination, green plants growing for further research



Field of Metrology and
Quality Control in Industry


Checking and calibration of industrial measuring gauges



Chemical – Industrial

Fertilizers, pesticides, detergents, paint, oil, etc.






The New Control System Offers

- 5.7 inch (14.5 cm) touch screen display
- Microprocessor fuzzy logic process control
- Intuitive control via colour icons
- Graphic configuration of a new program
- Transparent displaying of data course at the cycle
- Protective thermostat class 3
- Acoustic and visual alarm
- Multi-level users administration (corresponding to FDA 21 Part 11)
- Keyboard lock against unauthorised handling
- Data encryption and non-manipulability (corresponding to FDA 21 Part 11)
- Up to 100 programs and up to 100 segments for each program
- Yearly data logger in graphic and numeric form
- On-line or off-line data export
- Prepared service programs for fast diagnostics of faults
- Easy service diagnostics including remote access
- Multi-language communication
- Printing of protocols in PDF format via Warmcomm 4.0
- Easy user configuration of the device
- SD memory card, USB Host and RS 232 standardly included
- WIFI connection, USB device or Ethernet interface with own IP address for remote data transfer, control and diagnostics (optional equipment)
- Programming of ramps, real time and cycling
- Fan setting 10–100%
- Main ON/OFF switch for security reasons
- Device state LED indicator

Connectivity




Data Outputs

Thanks to the most up-to-date components of electronic, the device CLIMACELL® EVO does not have any data peripherals connection limit. The basic configuration contains traditional and reliable RS 232, USB Device and the SD card as the data carrier. The device can be easily extended with the Wifi 802.11b/g module with up to 100 meters reach, there is also available the USB Host for bi-directional USB communication and for remote connection there is the Ethernet (RJ 45) connection. Proper IP address allows easy connection to PC or selected printer, respectively other usual data periphery (Smartphone, Netbook, etc.). Thanks to the open platform and adjusted data format it is also possible to configure remote connection and to work with on-line data in remote mode (internet).



WarmComm 4.0

Universal Data Administration with Devices of the MMM Group



- connectible to all the devices of the MMM Group
- stable platform of the SQL library
- user-friendly environment
- Connection via the Ethernet to unlimited number of devices via RS 232,USB, then limited by the number of PC ports
- bilateral communication – data monitoring and device control
- compatibility with older lines of heat technology devices
- Client-Server architecture
- service module for local and remote diagnostics
- three levels depending on client's requirements (B-P-F)
- compliance with FDA CFR 21 Part 11 (version F)
- web support, on-line updates
- protected licence policy
- unpretentious to HW requirements, compatible with MS Windows
- validation documentation IQ/OQ



Comfort Machine with Superior Parameters

MMM Group offers traditionally fully ranged size of the cabinet, from personal size 111 litres, up to new size 1 212 litres, with the best ratio cost/performance. Patented vertical air flow with preheating chamber and asymmetrically perforated panels ensure the well proven vertical spiralled air flow with the best spatial homogeneity.

Deep experience of the factory engineers and many years of careful development help with sophisticated Fuzzy Logic control system. By means of the fuzzy logic are continually evaluated the current process conditions as size of chamber, set parameters, quantity of the samples inside and herewith optimizing heating, cooling and steaming performance.

High pressure steam generator in new easy accessible position and newly designed powerful freezing coil regulate the relative humidity quickly in full range from 10–98% RH, according the customer set, and without significant temperature interference.

Practical large and popular door handle, robust wheels with brakes and 220° (with exception of size 1212) openable main door(s) contributes to high user friendly character of the device. Light grey with light blue device colours highlighted by dark blue smiley control panel cause a pleasant feeling of harmony in the user every morning




Programmable Exposition Lighting

New generation of the CLIMACELL® EVO device offers wide possibilities of selected lighting use. The variability of placement, selection of light sources, user friendliness and possibility of fluent intensity control meet even the most demanding requirements towards applications with exposition lighting.

Fluorescent Tubes in Doors

Traditional placement of the light cassette with reworked design and increased lighting intensity (up to 36,000 LUX). Even exposition of the whole chamber section with the lowest purchase costs and minimal influence on conditions in the chamber. Regulation of intensity 10-100% in steps of 1%. It can be completed with intensity measuring. Suitable for industrial simulation of ageing or modest processes of growth simulations. Simulation of day and night conditions. Available for CLIMACELL® KOMFORT + CLIMACELL® EVO.








Fluorescent Tubes in Shelves

Vertical source of up to three light cassettes with direct lighting and variable height of exposure. Even exposition of the whole shelf and optimal use of the chamber volume for the sizes of surface lighting. Efficient balancing of temperature emissions thanks to perforation of cassettes and exact regulation of conditions in the chamber under full exposition. Maximal intensity 20,000 LUX (12 cm below the source). Regulation of intensity 10-100% in steps of 1%. It can be completed with intensity measuring. Typical for tests of photo stability or basic growth simulations in botany. Simulation of day and night conditions. Available for CLIMACELL® KOMFORT + CLIMACELL® EVO.




Various light source colours.



LED Lighting in Doors

Economic solution of white exposition LED lighting with high intensity (up to 21,000 LUX). Even exposition of the whole chamber section with low temperature emissions. Fluent regulation of intensity 10-100% in steps of 1%. Suitable for industrial testing with high requirements towards intensity. Simulation of day and night conditions. It can be completed with intensity measuring. Available for CLIMACELL® EVO.



LED Lighting in Shelves

Exact horizontal lighting with white or colour LED lighting with maximal intensity (up to 30,000 LUX), Low temperature emissions of light source, variability of illuminated cassettes placement and fluent regulation of intensity for each shelf in the range of 10-100% in steps of 1% offers the highest standard of light conditions simulation for industrial use or use in botany. Maximal use of illuminated surface of shelves in relation to the chamber volume. Simulation of day and night conditions. It can be completed with intensity measuring. Available for CLIMACELL® EVO.




Humidity Control

CLIMACELL® EVO is a climatic chamber – i.e. a device that is able to exactly and quickly regulate the quantity of humidity in the chamber. This is possible thanks to strong system of active increase and decrease of humidity in connection with the system of water supply to the device.

Steam Generator

The device allows steam generation and its precise dosing to the chamber. Thanks to our long-term experience in the field of steam sterilisation we succeeded to develop pressure steam generator able to increase relative humidity in the chamber in a precise, reliable and fast way. Steam overpressure is generated in the water reservoir using the heating element. Then, the valve releases exact volume of steam to the chamber. The technology eliminates the overshootings while reaching required level of relative humidity.



Humidity Reduction

Unlike many other manufacturers we are not engaged only in humidity increase, but we also focus on active humidity decrease, using the separate cooling snake of the cooling system. The control system of CLIMACELL® EVO is able to reduce humidity in the chamber using the cooling system while keeping a nearly constant temperature. Humidity condensates on



freezing element and condensed water is drained back to the waste receptacle, being pumped to the drain from there. Thanks to the efficient system CLIMACELL® EVO reaches even the low relative humidity values very quickly.




Water Intake and Use

In order to create the humidity exactly and reliably in the long term, the steam generator of CLIMACELL® EVO operates only with demineralized water. The access to such water can be solved in two ways. A standard solution means that you pour demineralized water to a barrel, delivered with each CLIMACELL® EVO and you connect the pump from the barrel to the connector on the rear side of the device. The other possibility includes connection of demineralized water intake from the laboratory water distribution system to the steam generator of CLIMACELL® EVO via reduction pressure valve. In both cases, the device automatically takes exact quantity of water as needed for humidity creation in the steam generator.



Restrictions of Temperature and Relative Humidity Setting Combinations



Accessories Included

Each CLIMACELL® EVO is supplied with standard equipment which does not have to be additionally ordered and it makes a standard part of delivery:



Touch screen



Communication ports RS 232 and USB host



SD card



Steam generator, humidity control



Water barrel for demineralized water



Reliable RH sensor



Multi-conductor temperature sensor



Sealing inner glass door

Optional Equipment

Thanks to modular construction of our devices even CLIMACELL® EVO may be additionally equipped according to your preferences with many additional options. CLIMACELL® EVO may then serve as a chamber for testing of photo-stability, light simulation of day and night, processes with CO₂ control, hot-air decontamination, etc.

1. Hot-air decontamination 160°C
2. Additional cooling -20°C
3. Flexible temperature sensors
4. LED light shelves
5. Exposition lighting in doors
6. Light sensors of exposition
7. Defrosting system
8. CO₂ control
9. Software WarmComm 4,0
10. Data module USB device, Ethernet, wi-fi
11. Mechanic door lock
12. Electromagnetic door lock
13. Trays or shelves
14. Access port Ø 25, 50, 100 mm
15. Programmable inner socket
16. External printer
17. Multi-point temp. / humidity measuring
18. IQ/OQ protocols




1



2



3



4




5




6



7



8




9



10




11



12



13



14



15



16



17



18

Technical Parameters



CLIMACELL® EVO (CLC EVO) 111, 222, 404, 707, 1212						
Technical data Internal space – chamber, stainless steel DIN 1.4301 (AISI 304)	volume	cca l	111	222	404	707
	width	mm	540	540	540	940
	depth	mm	380	530	530	530
	height	mm	535	765	1415	1415
Volume of the steam space		cca l	167	305	530	878
External dimensions (including door, handle and caster)	width	mm	780	780	1100	1500
	height (incl. caster)	mm	1187	1450	1890	1890
	depth	mm	755	885	885	885
Package – dimensions	width	cca mm	992	1120	1332	1682
	height (incl. palette)	cca mm	1650	1746	2200	2190
	depth	cca mm	954	952	1062	1064
Weight CLC EVO 0°C	net	cca kg	110	143	240	280
	brut	cca kg	220	263	390	500
Weight CLC EVO -20°C	net	cca kg	120	153	250	290
	brut	cca kg	230	273	400	510
Shelves of stainless steel *	shelves	max. No.	7	10	19	19
	standard equipment	pcs. included	2	2	2	2
	min. distance between shelves	mm	70	70	70	70
	Storage area (w x d)	mm	520x335	520x485	520x485	920x485
Maximal load *)	per 1 tray	kg/screen	20	30	30	50
	for a shelf	kg/shelf	20	30	30	20
	total inside of device	kg/case	50	70	100	130
Number of outer metal doors		psc.	1	1	1	2
Number of inner glass doors		psc.	1	1	1	2
Electricity	max. power 0°C	W	2000/2200**	2200/2300**	2700/2700**	3000/3050**
	max. power -20°C	W	2000/2200**	2200/2300**	2700/2700**	3600/3650**
	mains 50/60 Hz	V	115/230	115/230	115/230	115/230
Protective system			IP 20	IP 20	IP 20	IP 20
Temperature data	from 0.0°C	to °C	100 (decontamination 160 °C)			70
Working temperature	from -20.0°C	to °C	100 (decontamination 160 °C)			70
Temperature accuracy	in space at 10°C	cca (±) °C	<0,5	<0,5	<1	<0,9
	at 37°C	cca (±) °C	<0,5	<0,5	<1	<0,5
	in time	cca (±) °C	<0,2	<0,2	<0,3	<0,4
Heating/up time to 37°C from the ambient temperature		min	<11	<11	<22	<13
Cooling/down time from 22°C to 10°C	0 °C	min	<21	<17	<19	<21
	-20 °C	min	<11	<14	<21	•
Recovery time after 30 s of door opening according to DIN 12 880	při 37 °C	min	<4	<3	<3	<6
	při 50 °C	min	<5	<6	<7	<6
Relative humidity CLC EVO	range	%	10-98	10-98	10-98	10-98
Accuracy RH (T _{chamber} ≥ 21°C)	in time	%	< 2	< 2	< 2	< 2
Heat emission	at 37°C	cca W	70	63	123	148
Complete device noise level		dB	46/52	50/56	56/58	58/65
CO ₂ concentration		%	0,1-20			-
Required pressure CO ₂		bar/psi	0,3-0,7/5-10			0,3-0,7/5-10

Note: All technical data are related to 22°C ambient temperature and ± 10% voltage swing (if not specified).
For other parameters see section Electric connections.

- not measured
- *) Approx. 50% of the tray area can be filled in a way a uniform air circulation is enabled inside the chamber.
- **) Value at cooling up to -20°C.

The values may differ depending on specific charge and media parameters.
Change in the design and make reserved.



Make Acquaintance With Our Further Offers ...

Laboratory Ovens and Incubators



INCUCELL® / INCUCELL® V
Suitable for safe treatment
of microbiological cultures

FRIOCELL®
Cooling incubators

CLIMACELL®
Climatic chambers

CO2CELL
CO₂ atmosphere

ECOCELL®
The highly cost-effective heating oven
series for simple drying processes

DUROCELL
Special- purpose drying ovens
DUROCELL with highly resistant
EPOLON coating

VACUCELL®
Vacuum drying ovens

STERICELL®
Intended for hot air sterilization of
materials under specified temperature
and duration.

VENTICELL®
Drying ovens with forced air circulation

Sterilization and Depyrogenation




VENTICELL® IL
series of modular large-sized laboratory devices with the chamber
volume of from 700 to 3 900 liters. The devices are used for
items sterilization at the temperature of up to 180°C, or for items
depyrogenation at the temperature of up to 300°C and optional time
mode. The devices can be used in laboratories, industry, pharmacy and
research.

Steam Sterilizers (Autoclaves)



STERILAB®
Small steam sterilizer, 25 l



UNISTERI® HP IL
Medium-sized steam sterilizers, 73–254 l



STERIVAP® HP IL
Large steam sterilizers, 148–1 490 l

