# SIMDOS 02

### Dosing pump for liquids

- ▶ Simple and intuitive operation
- ▶ Easy calibration
- ▶ Cycle mode
- Adaptable to fluid characteristics
- ▶ Self priming, can run dry
- ▶ Analog and impulse control (RC)
- ▶ Splashproof IP65, small footprint

# Fields of application

- Chemistry
- Synthetic organic chemistry
- Pharmacy
- Adhesives and glue
- Polymers & polymer coating
- Food technology research
- Detergents

# Hydraulic data

Flow rate	Dosing volume	Suction height	Max. pressure
30 μl/min–20 ml/min	30 μl–999 ml	2 mWg	6 bar

## Chemical resistance

Code	Pump head	Diaphragm	Valves	Filter
KT	PP	PTFE covered	FFKM Kalrez <sup>®</sup>	PEEK
TT	PVDF	PTFE covered	FFKM Kalrez <sup>®</sup>	PVDF
FT	PTFE	PTFE covered	FFKM Kalrez <sup>®</sup> *	PEEK
ST	STAINLESS STEEL	PTFE covered	FFKM Kalrez <sup>®</sup> *	PEEK

 $<sup>^*</sup>$ On request FFKM Chemraz  $^{^\circledR}$ 

#### **Functions**

S - Version	RC - Version		RC Plus - Version
Manual operation	<ul> <li>Manual operation</li> <li>Analog control: 0–5 V, 0–10 V, 0–20 mA, 4–20 mA, from 1 to 100%</li> <li>Start/Stop through logic control (TTL)</li> </ul>	<ul> <li>Reset/Prime through logic control (TTL)</li> <li>Output signal fault alarm</li> <li>Cable for external control included</li> </ul>	<ul><li>Same as RC</li><li>Plus RS 232</li></ul>

#### Technical data

- Main supply 100-240 V / 50-60 Hz
- Ambient temperature allowed +5 to +40 °C
- Liquid temperature allowed +5 to +80 °C
- Maximum viscosity allowed 150 cSt
- Accuracy +/-2% (nominal value)
- Repeatability +/-1%

- Power consumption 10 W
- Protection class IP65
- Dimensions: 140 x 87 x 130 mm
- Weight: 0.9 kg
- Hydraulic connection UNF 1/4"-28
- Filter



# SIMDOS 02

# Accessories

## Valves kit

	ID-Nr.
Chemraz <sup>®</sup>	164984
special valves for certain chemicals	



⚠ Special Valves CHEMRAZ®

# Diaphragm pressure control valve with support when the feeding tank is above the pump

	ID-Nr.
Kit JFDV 30 KTZ	166286
Kit JFDV 30 TTZ	166287
Kit JFDV 30 FTZ	166288



### Filter

Тур	Material	Connector	ID-Nr.
FS 60 T	PVDF	UNF 1/4"-28	165210
FS 60 X	PEEK	UNF 1/4"-28	165212



## Connection tube

	ID-Nr.
Tube 1/16" with connector UNF 1/4"-28, 1 m for fine dosing	166335



# Mounting plate

	ID-Nr.
for wall mounting	160473



## Standfitting

	ID-Nr.
for retort stand	160474



## **Footswitch**

	ID-Nr.
for impulse start and stop	155872



